

## ELHR12V65AH




### Specification

<b>Nominal Voltage</b>	12V	
<b>Nominal Capacity(20HR)</b>	65.0AH	
<b>Dimensions</b>	Length	348±3mm (13.2 inches)
	Width	167±2mm (6.57 inches)
	Container Height	178±2mm (7.01 inches)
	Total Height (with Terminal)	178±2mm (7.01 inches)
<b>Approx Weight</b>	Approx 19.2 kg (42.3 lbs)	
<b>Terminal</b>	T6	
<b>Container Material</b>	ABS	
<b>Rated Capacity</b>	65.0 AH/3.25A	20hr ,1.80V/cell, 25°C/77°F)
	62.1 AH/6.21A	(10hr,1.80V/cell, 25°C/77°F)
	53.6 AH/10.72A	(5hr,1.75V/cell, 25°C/77°F)
	45.8 AH/15.3A	(3hr,1.75V/cell, 25°C/77°F)
	37.5AH/37.5A	(1hr,1.60V/cell, 25°C/77°F)
<b>Max. Discharge Current</b>	780A (5s)	
<b>Internal Resistance</b>	Approx 7.3mΩ	
<b>Operating Temp.Range</b>	Discharge : 1~50°C (5~122 F)	
	Charge : 0~40°C (32~104°F)	
	Storage : -15~40°C (5~104°F)	
<b>Nominal Operating Temp. Range</b>	25.±3°C (77±5°F)	
<b>Cycle Use</b>	Initial Charging Current less than19.5A.Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
<b>Standby Use</b>	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
<b>Capacity affected by Temperature</b>	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%

### Applications

- All purpose
- Uninterruptable Power Supply (UPS)
- Electric Power System (EPS)
- Emergency backup power supply
- Emergency light
- Railway signal
- Aircraft signal
- Alarm and security system
- Electronic apparatus and equipment
- Communication power supply
- DC power supply
- Auto control system



### Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	114.0	87.6	75.5	65.6	50.8	37.8	30.6	18.5	14.2	11.78	10.04	8.79	7.11	5.98	3.20
1.80V/cell	142.7	102.5	85.9	73.8	55.7	40.8	32.7	19.7	14.9	12.34	10.47	9.16	7.40	6.21	3.25
1.75V/cell	160.9	111.8	93.8	79.0	58.7	42.8	34.2	20.4	15.3	12.65	10.72	9.35	7.51	6.27	3.29
1.70V/cell	177.1	120.7	100.1	82.9	61.4	44.3	35.6	21.1	15.8	12.96	10.97	9.53	7.62	6.33	3.32
1.65V/cell	193.8	130.0	105.1	86.17	63.3	45.8	36.6	21.6	16.2	13.23	11.18	9.70	7.73	6.408	3.37
1.60V/cell	210.1	138.2	109.3	89.4	65.0	47.4	37.5	22.1	16.6	13.49	11.38	9.84	7.83	6.48	3.38

### Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	208.5	161.7	140.9	123.6	96.8	72.7	59.1	35.9	27.7	23.0	19.7	17.28	14.04	11.83	6.34
1.80V/cell	258.1	187.0	158.1	137.0	104.6	77.9	62.8	37.9	29.0	24.0	20.4	17.93	14.56	12.27	6.43
1.75V/cell	284.8	200.8	170.5	145.3	109.3	80.9	65.3	39.3	29.6	24.5	20.9	18.24	14.74	12.38	6.50
1.70V/cell	304.9	211.9	179.5	151.4	113.6	83.4	67.7	40.4	30.4	25.1	21.3	18.58	14.94	12.49	6.56
1.65V/cell	328.8	226.2	186.9	156.0	116.3	85.4	69.1	41.2	31.1	25.5	21.6	18.84	15.13	12.61	6.64
1.60V/cell	348.4	235.0	191.2	160.3	118.4	87.9	70.5	41.9	31.6	25.9	21.9	19.07	15.30	12.74	6.66