

SIGNATURE[™] Collection

Surface designer Series


Туре:	
Project/Location:	
Contractor:	
Prepared By:	
Date:	
Model No.:	

FEATURES

- Available in 1, 2 or 3 head configurations
- Highly resistant powder-coated, die cast aluminum construction
- MR16 halogen lamps: 6W, 10W, 12W, 20W, 35W and 50W MR16 LED lamps: 4W, 5W and 6W
- CSA certified to C22.2 No. 141-15 See warranty details at: www.tnb.ca/en/brands/lumacell



DIMENSIONS Dimensions are approximate and subject to change



TYPICAL SPECIFICATIONS

The contractor will supply and install **Lumacell[®] Signature™** Collection Series remote heads. These remote heads will consist of either single, double or triple head configurations according to the design. Remote heads will be constructed of durable powder coated, Die-Cast aluminum and use MR16 halogen light sources.

The remote fixtures shall be certified to CSA C22.2 No.141-15. The unit shall be **Lumacell®** model:

WIRE GUARDS

460.0029-L	Wall Mount (DR1130)	
460.0032-L	Wall Mount (DR2130)	
460.0078-L	Wall Mount (DR3130)	

REPLACEMENT LAMPS

MODEL	LAMP TYPE	VOLTAGE-WATTAGE	
580.0074-L	MR16 flood	6V-6W	
580.0080-L	MR16 flood	12V-12W	
580.0077-L	MR16 flood	24V-20W	
580.0097-L	MR16 LED	6V-4W	
580.0093-L	MR16 LED	12V-4W	
580.0104-L	MR16 LED	2V-5W	
580.0098-L	MR16 LED	24V-4W	
580.0100-L	MR16 LED	24V-6W	
580.0113-L	MR16 LED	120V-4W	
580.0106-L	MR16 LED	12V-6W	

See the complete list p. 152-154.

ORDERING INFORMATION

SERIES	# OF HEADS	HEAD STYLE	COLOUR	LAMP STYLE	VOLTAGE/WATTAGE	
DR= decorative remote	1= single head 2= double head 3= triple head	130= closed	BK= black WH= white	MR16=MR16 LED lamp	LD1= MR16 LED, 6V-4W LD7= MR16 LED, 12V-4W LD9= MR16 LED, 12V-5W LD10= MR16 LED, 12V-6W LD13= MR16 LED, 24V-4W LD14= MR16 LED, 24V-6W LD25= MR16 LED, 120V-4W 6V6W= MR16 halogen, 6V-6W 6V10W= MR16 halogen, 6V-10W 12V12W= MR16 halogen, 12V-12W	12V20W = MR16 halogen, 12V-20W 12V35W = MR16 halogen, 12V-35W 12V50W = MR16 halogen, 12V-50W 24V12W = MR16 halogen, 24V-12W 24V20W = MR16 halogen, 24V-20W 24V35W = MR16 halogen, 24V-35W 24V50W = MR16 halogen, 24V-50W 12V20WH = MR16-IR, 12V-20W, high output 12V35WH = MR16-IR, 12V-35W, high output

EXAMPLE: DR1130WH-MR166V6W





